

THE SP03 IS IDEAL FOR:

- Private vehicle
- Company vehicle
- Fleet
- Construction
- Private investigator



SP03

FEATURES

Tracked by

SMS, APP, Web Reports location in real time through different interfaces

Remote cut-off (petrol/power)

Compel the vehicle to stop by breaking off the fuel connection

Built-in 6000mAh battery

High capacity Li-ion battery ensuring sufficient power supply

Optional for wiring or portable

Able to switch from wiring to portable as this model have big capacity built in battery

SOS button

Activate the emergency notification to user

Configurable tracking modes

Location uploaded following fixed distance, time interval, preset cornering

Multiple alarms

Instant alert for towing, vibration, over speed, power off, geo-fence

Voice monitoring

Activate listen-in mode via text

SPECIFICATIONS

Content	Specification
Dimensions	94mm x 60mm x 38mm
Weight	300g
Network	GSM/GPRS
Band	850/900/1800/1900Mhz
GPS Sensitivity	-159dBm
GPS Accuracy	5m
GPS Start time	Cold status 45s Warm status 35s Hot status 1s
Voltage	12 V -24V
Backup battery	Chargeable 3.7V 6000mAh Polymer Li-ion Battery
Charge Current	1A±0.2A
Storage Temp.	-40°C to +85°C
Operation Temp.	-20°C to +65°C
Humidity	5%~95% non-condensing

CERTIFIED

FCC CE RoHS

Contact us:

sales@stopanik.com

www.stopanik.com

Stopanik Sdn Bhd (1250881-P)

73-1 Jalan Nautika B U20/B,
Section U20, Pusat komersil TSB
Sungai Buloh 40160 Selangor, Malaysia

Free download mobile app from

