





THE SP05 IS IDEAL FOR:

-  Private motorcycle
-  Company motorcycle

SP05

FEATURES

Tracked by:

SMS, APP, Web Reports location in real time through different interfaces

Remote cut-off (petrol/power)

Compel the vehicle to stop by breaking off the petrol/power connection

Intelligent power management

Reduce inefficient power consumption when device stay idle

Vehicle battery protection

Never drain out of the battery of motorcycle for optimal protection

ACC detection for ignition status

Be aware of the ignition status whenever you need

Configurable tracking modes

Location uploaded following fixed distance, time interval, preset cornering

Multiple alarms

Instant alert for vibration, over speed, power off, geo-fence

SPECIFICATIONS

Content	Specification
Dimensions	67mm x 38.8mm x 11.5mm
Weight	125g
Network	GSM/GPRS CLASS12,TCP/IP
Band	850/900/1800/1900Mhz Quad band for global world
GPS Sensitivity	-159dBm
GPS Accuracy	5m
GPS Start time	Cold status 38s Hot status 2s
Voltage input range	9 V - 40 V
Backup battery	Chargeable 3.7V 120mAh Polymer Li-ion Battery
Operation Temp.	-30°C ~ +70°C
Humidity	20% - 80% RH

CERTIFIED

FC CE RoHS

Contact us:

 sales@stopanik.com

 www.stopanik.com

Stopanik Sdn Bhd (1250881-P)

73-1 Jalan Nautika B U20/B,
Section U20,Pusat komersil TSB
Sungai Buloh 40160 Selangor, Malaysia

Free download mobile app from

